



CLAIMS 09/779,594

1. [CURRENTLY AMENDED] In a vehicle having a right and left side and substantially massive components, and having at least one fixed body member connected with substantial rigidity to substantially all of the substantially massive components of said vehicle, a vehicle structure having an operating position attained during normal driving conditions and an extended position attained at the time of ~~passenger and operator~~occupant access to the vehicle, said vehicle structure having a means to divert the impact energy in lateral impacts to be absorbed by said vehicle through the at least one fixed body member while releasing the ~~passengers and operators~~occupants each having mass, weight, left and right sides, a back and a bottom, to move independently of said vehicle, in a passenger support mechanism with a plurality of elements in a predetermined controlled fashion, in order to minimize injury to such ~~operators and passengers~~occupants.

2.[CURRENTLY AMENDED] The vehicle structure of claim 1, further comprising:

- ~~b)~~a) at least one pair of secondary slides each with a first face and a second face, attached by said first face to the at least one fixed body member on the left side and the right side of the vehicle respectively, the members of each pair being mounted at the same longitudinal position of said vehicle;
- ~~e)~~b) a plurality of passenger support mechanisms each having ejecting elements ~~and non-ejecting elements and~~ each of said passenger support mechanisms mounted in pairs on each of the left and the right sides of the said vehicle on at least one lateral axis;

c) at least one pair of a safety beam lower element each member of said pair fixedly connected to said non-ejecting elements of the passenger support mechanisms, and each of said safety beam lower element having a first face and a second face, and said second face attached to the second face of said secondary slides such that, each of said safety beam lower element are normally fixedly attached by said second face to the second face of a member of said pair of secondary slide, but become decoupled and thereafter slidably attached by said second face to said secondary slides along a lateral axis when a lateral shear force greater than a predetermined force is applied to said first face relative to said second face of said secondary slides allowing said safety beam lower element attached to said second face of said secondary slides to slide along said lateral axis relative to said secondary slides, said safety beam lower element mounted on each of said secondary slides being constructed such that after they are decoupled, they can be guided laterally by, and are slidably attached to at least one member of a pair of said secondary slides and further positioned on the said secondary slides at all times such that they are not obstructed by any elements of the vehicle in the event that said safety beam lower element need under collision conditions to traverse the center of the vehicle to the further side of the vehicle;

d) at least one pair of an safety beam upper element each member of said pair having a first face and a second face, and each of the members of said pair mounted with its first face to the first face of each member of said pair of said safety beam lower element on the left and the right sides of the vehicle, and fixedly attached by said second face to the ejecting elements of one of the passenger support mechanisms

~~De~~ at least one shock-absorbing device and at least one force distributing protector shield

both installed to protect each of the pair of passenger support mechanisms, on each of the left and right sides of the vehicle, and locked to the fixed body members of the vehicle when in the operating position; and

- f) internal airbags, each mounted on the outer side of each of said passenger support mechanisms, but inside said shock absorbers and protector shields, on both the left and the right sides of the vehicle, such that upon detection of an impact event, the airbag deploys next to said passenger support mechanism(s) ~~and deploying upwards~~ and ~~inwards~~ to protect the ~~passengers~~ occupants.

3. **[CURRENTLY AMENDED]** The vehicle structure of claim 2, wherein said ~~non-ejecting elements of said passenger support mechanisms comprise the inner arm rest and other elements of the passenger support mechanism supporting the passenger on the inner side of the vehicle and wherein said ejecting elements of said passenger support mechanisms comprise the outer arm rest and other elements of the passenger support mechanism supporting the passenger on the entry side of the vehicle.~~

4. **[CURRENTLY AMENDED]** The vehicle structure of claim 2, ~~wherein said non-ejecting elements~~ further comprising a non ejecting element of said passenger support mechanisms consist of a null set of elements and the ejecting elements of the passenger support mechanism consist of all elements of the passenger support ~~mechanisms~~ mechanism attached to said safety beam lower element.

5. **[Withdrawn]** The vehicle structure of claim 2, wherein said internal airbags are preinflated to a predetermined pressure.



6. **[Withdrawn]** The internal airbags of claim 5, further comprising supplementary porous filling materials within said internal airbags thereby changing the compression characteristics of said internal airbags under impact.

7. **[Withdrawn]** A method of designing a passenger vehicle, comprising the sequence of:

- a) designing a human environment that provides more than a minimal expected crash injury level, physical comfort and utility;
- b) designing a vehicle that hosts said human environment to meet vehicle performance characteristics,

thereby providing a “bottom up” design paradigm that targets human safety and utility as a priority.

8. **[Withdrawn]** A method for impact protection of passengers in a vehicle by minimizing the intrusion of the impacting body into the passenger space and minimizing the peak impact acceleration transferred to said vehicle.

9. **[ORIGINAL]** The vehicle structure of claim 2, wherein said ejecting elements comprise one or more of the elements of said passenger support mechanism that support the back, left side and right side of said passenger, said ejection providing a means for passenger egress and ingress.

10. **[ORIGINAL]** The vehicle structure of claim 9, wherein said ejection comprises, a downward movement.



11. [ORIGINAL] The vehicle structure of claim 9, wherein said ejection comprises, a rearward movement.

12. [ORIGINAL] The vehicle structure of claim 2, wherein said ejecting elements comprise one or more elements supporting the pelvis and upper legs of said passenger, said ejection providing a means for passenger egress and ingress.

13. [ORIGINAL] The vehicle structure of claim 12, wherein said ejection comprises, an upward movement.

14. [ORIGINAL] The vehicle structure of claim 12, wherein said ejection comprises, a forward movement.

15. [ORIGINAL] The vehicle structure of claim 2, wherein said ejecting elements comprise all support elements for the passenger, and wherein ejection raises the said ejected elements such that they can be subsequently be either translated or rotated over the sill of the vehicle side to allow egress and ingress of said passenger.

16[ORIGINAL] The vehicle structure of claim 1, further comprising:

- a) at least one pair of secondary slides each with a first face and a second face, attached by said first face to the at least one fixed body member on the left side and the right side of the vehicle respectively, the members of each pair being mounted at the same longitudinal position of said vehicle;
- b) a plurality of passenger support mechanisms each having two interlocking parts consisting of an ejecting element that may be displaced to facilitate egress and ingress, and non-ejecting element and each of said passenger support mechanisms mounted in pairs on each of the left and the right sides of the said vehicle on at least



one lateral axes said non-ejecting element of each passenger support mechanism, having a support face attached to the second face of said secondary slides such that, each of said non-ejecting elements of said passenger support mechanisms are normally fixedly attached by said support face to the second face of a member of said pair of secondary slide, but become decoupled and thereafter slidably attached by said support face to said secondary slides along a lateral axis when a lateral shear force greater than a predetermined force is applied to said first face relative to said second face of said secondary slides allowing said non-ejecting elements of said passenger support mechanism to detach from said secondary slides and slide along said lateral axis relative to said secondary slides, said non-ejecting elements of the passenger support mechanism mounted on each of said secondary slides being constructed such that after they are decoupled, they can be guided laterally by, and are slidably attached to either member of a pair of said secondary slides and further positioned on said secondary slides at all times such that they are not obstructed by any elements of the vehicle in the event that said element of the passenger support mechanism need under collision conditions to traverse the center of the vehicle to the further side of the vehicle, said two interlocking parts of said passenger support mechaism being locked together while the vehicle is in operation and unlocked for egress and ingress of the passenger;

- c) at least one shock-absorbing device and at least one force distributing protector shield both installed to protect each member of the pair of passenger support mechanisms, on each of the left and right sides of the vehicle, said force distributing protector



shield being pivotally mounted to the fixed members of the vehicle and locked to the fixed body members of the vehicle when in the operating position; and

- d) preinflated internal airbags with a first face and a second face, the first face mounted on the outer side of each of the ejecting elements of the passenger support mechanism, and said second face attached to said shock absorbers and protector shields, on both the left and the right sides of the vehicle, such that upon detection of an impact event, the airbag deploys next to said passenger support mechanism(s) and deploying upwards and inwards to protect the passengers.

17. **[Withdrawn]** In a vehicle having a vehicle structure comprising a right and a left side an independantly ejectable mechanism for each of said passenger support mechanisms, wherein:

- a) said independently ejectable mechanisms for the passenger support mechanisms on the left side of the vehicle are mounted indirectly to fixed body members on the left side of said vehicle to allow said passenger support mechanisms on the left side of the vehicle to eject by one of: sliding along a lateral axis to a position substantially outside and adjoining the vehicle; rotating to face substantually outside the vehicle; extending to face substantially outside the vehicle and moving outwards from the vehicle, to a position substantially adjoining the vehicle on the left side thereby allowing said passengers that ride on said passenger support mechanisms on the left side of said vehicle to egress and ingress from the left side of the vehicle by ejecting said independently ejectable mechanisms; and



b) ~~§~~ said independently ejectable mechanisms for the passenger support mechanisms on the right side of the vehicle are mounted indirectly to fixed body members on the right side of said vehicle to allow said passenger support mechanisms on the right side of the vehicle to eject by one of: sliding along a lateral axis to a position substantially outside but adjoining the vehicle; rotating to face substantially outside the vehicle; extending to face substantially outside the vehicle and moving outwards from the vehicle, to a position substantially adjoining the vehicle on the right side thereby allowing said passengers that ride on said passenger support mechanisms on the right side of said vehicle to egress and ingress from the right side of the vehicle by ejecting said independently ejectable mechanisms.

18. **[Withdrawn]** The vehicle structure of claim 17, wherein said passenger support mechanisms each further comprise a multi-element adjustable seat that provide a means for support to the body of said passenger and a removeable and lockable safety harness that is mounted with safety harness supports to said multi-element adjustable seat to deploy a surface that will protect and support predetermined parts of the human body when the vehicle sustains rapid changes in velocity, and wherein said safety harness supports are removable and lockable on at least one support point and pivotally supported on at least one support point to allow passenger to mount and dismount the said multi-element adjustable seat.

19**[Withdrawn]** The vehicle structure of claim 17, wherein said multi-element adjustable seat includes an adjustable section near the head and neck which supports said pivotally mounted safety harness supports, thereby allowing said safety harness to be released at the removable and lockable safety harness supports, to swing on said pivotally



mounted safety harness supports, up and over the head of the passenger to allow the passenger access to said multi-element contoured seat.

20[**Withdrawn**] The vehicle structure as in claim 19, wherein said safety harness comprises:

- a) a pair of harness support arms that are pivotally attached to the passenger support mechanism in the vicinity of the head rest on either side, said harness support arms being spring mounted to raise the harness when removed for egress and ingress;
- b) telescoping sections with a first end and a second end, wherein said first end is attached to each of said harness support arms and with said second end attached to a protective shield that is designed to protect the head and neck under collision conditions;
- c) harness lower sections that are attached to the lower end of said protective shield and lock into the inner sides of the arm rests or the sides of said passenger support mechanisms;

thereby providing a support surface under frontal impact for the head neck and torso, and providing easy access for egress and ingress when released from the locks at the harness lower section.



21[**Withdrawn**] The vehicle structure of claim 17, wherein said multi-element adjustable seat supports said pivotally mounted safety harness, and wherein said safety harness comprises driving controls mounted on its front surface away from the passenger.

22. [**Withdrawn**] The vehicle structure of claim 17, wherein said ejectable multi-element adjustable seat comprises arm rests with operational controls for driving said vehicle.

23. [**Withdrawn**] In a vehicle with the region immediately below the windshield being substantially clear of instrumentation and controls, a computer controlled display system arranged to be immediately below said windshield to project information of interest to the driver, thereby providing an image that relates to the driving conditions as viewed by the driver in the windscreen.

24. [**Withdrawn**] A computer controlled display system as in claim 23, wherein said display system projects at least one of position and velocity information with substantially the same orientation with regard to spacial position, direction and velocity from the perspective of the driver, with regard to what is seen by the driver in the windshield,, thereby providing a mechanism for reference to said information with minimal physical motion of the head, and minimal mental processing for relative orientation of the display relative to the view in said windshield.

25. [**Withdrawn**] A Passive Air Cushion System for protecting one or more protected entities, from impact from an impacting object comprising:

- a) an impacted structure in the vicinity of said protected entity;
- b) at least one sacrificial chamber located in a predetermined position within said impacted structure, such that said impact from impacting object, will compress said sacrificial chamber, said sacrificial chamber being filled with a compressible fluid;



- c) one or more fluid paths with flow control mechanisms, that are connected to said sacrificial chamber, and filled with said compressible fluid, such that under impact to the sacrificial chamber, said fluid paths may conduct a predetermined controlled volume of said compressible fluid out of said sacrificial chamber to predetermined locations;
- d) one or more micro-air cushions placed in locations in the vicinity of said protected entity and supported by said impacted structure, said micro-air cushions being connected to one or more of said fluid paths, thereby receiving predetermined controlled volumes of said compressible fluid from said fluid paths at and immediately following said impact;

thereby said sacrificial chamber inflating said micro-air cushions and protecting said protected entity.

26. **[Withdrawn]** A Passive Air-cushion System as in claim 25, wherein said sacrificial chambers and Micro Air-cushions are constructed as adjoining micro chambers within an airbag, thereby providing visco-elastic impact energy absorption when said air bag is compressed only in selected location that compress some but not others of the micro chambers thereby inducing a transfer of air or other compressible fluid under controlling viscous forces from some of said micro chambers that act as sacrificial chambers to others of said micro chambers that act as micro-air cushions.

27. **[Withdrawn]** A Passive Air-cushion System as in claim 26, wherein said micro-chambers are inflated prior to impact from a common source which is isolated by one way valves that close following inflation, thereby isolating the micro chambers of said Passive Air-cushion System

28. **[Withdrawn]** A Passive Air-cushion System as in claim 25, wherein the protected entity is the head and neck of a passenger, the impacted object is a vehicle, and the impacting object impacts the vehicle from the rear of said vehicle, and wherein said



sacrificial chamber is mounted in a position that will compress on impact by the impacting object, thereby said Passive air-cushion system protecting said passenger from whip-lash injury.

29. **[Withdrawn]** A Passive Air-cushion System as in claim 28, wherein said sacrificial chamber is located behind seat support members and in front of support elements for the seat that are rigidly attached to the vehicle fixed members, and wherein said seat support members are rigidly attached to said support elements for the seat but detach from said support elements following a rear impact to said vehicle resulting from the acceleration of the inertial mass of the passenger and seat, and are thereafter slidably attached to said support elements, and thereby compress said sacrificial chamber.

30. **[Withdrawn]** Two or more Passive Air-cushion Systems as in claim 25, consisting of a First set of Passive Air-cushion Systems and a Second Set of Passive Air-cushion systems, wherein the sacrificial chambers of said Second Set of Passive Air-cushion systems are mounted adjacent to the Micro Air-cushions of said First Set of Passive Air-cushion Systems, such that on inflation of the Micro Air-cushions of said First Set of Passive Air-Cushion Systems, the sacrificial chambers of said Second Set of Passive-Air-Cushion systems are compressed, thereby creating a cascaded system of Passive Air-cushion Systems to protect one or more protected entities in the vicinity of said micro-air cushions of said Second set of Passive Air Cushion Systems.

31. **[Withdrawn]** The vehicle structure of claim 1, wherein said means to move independently of said vehicle, said passenger support mechanism with a plurality of elements in a predetermined controlled fashion, comprises at least one auxiliary brake with a first braking surface and a second braking surface, said first braking surface being fixedly attached at and immediately following impact to said passenger support mechanism, and said second braking surface being attached at and immediately following impact to said at least one fixed body members of said vehicle.

32. **[Withdrawn]** The vehicle structure of claim 23, wherein said internal airbags are preinflated to a predetermined pressure.

33. **[Withdrawn]** The internal airbags of claim 23, further comprising supplementary porous filling materials within said internal airbags thereby changing the compression characteristics of said internal airbags under impact.

34. **[Withdrawn]** The vehicle structure of claim 1, wherein said passenger support mechanisms comprise pressure memory capable materials on the surfaces that are in contact with passengers thereby enhancing the comfort and safety of passengers.

35. **[Withdrawn]** The structure of claim 1, further comprising a safety foot switch fixedly attached to said passenger support mechanism, and positioned in the vicinity of said passenger's feet and programmed to controls the movement of the passenger support mechanism between said access position and said operating position, thereby providing passenger control of movement of said passenger support mechanism.

36. **[Withdrawn]** A vehicle structure as in claim 23, further comprising shockabsorbing devices that are fixed to the safety beam upper element at one end and fixed to the locking devices that bind the safety beam upper element and the attached components to the at least one fixed body members of the vehicle when the vehicle is operational, thereby providing a means for the safety beam upper element to move in a controlled predetermined fashion outwards on the far side during a lateral impact, when the locking devices are secured.



37. **[Withdrawn]** A vehicle structure as in claim 23, further comprising a flexible stretchable or folded material that is bound to the edges of the protector shield of the vehicle on one of its edges on such edges of protector shield that would normally make contact with the vehicle body, the other edge of the flexible stretchable or folded material is bound to a frame that locks to the vehicle body under operating conditions, thereby providing a membrane that can hold in body extremities preventing ejection on the far side under side impact, but also allowing storage of said material in a compressed or folded fashion under normal egress and ingress beside the frame along with the protector shields with door impact decouplers that fracture or disengage under impact.

38. **[Withdrawn]** A vehicle structure as in claim 2, further comprising deflation devices that deflate said internal airbags installed on the side of said vehicle away from said lateral impact, immediately following an impact, when an outward movement of said passenger support mechanisms is detected, thereby providing more space for the motion of said passenger support mechanisms following said impact and minimizing ejection of said passenger support mechanism outside said vehicle.

39 **[WITHDRAWN/PREVIOUSLY_RENUMBERED]** The vehicle structure of claim 1, further comprising:

- a) at least one pair of a safety beam lower elements said pair comprising two members of said pair, each member of said pair having a first face and a second face, and constructed to provide a means to resist compressive lateral impact forces, and to provide support for components attached thereto, a member of each pair of said safety beam lower elements being directly mounted on its second face to the at least one fixed body member, such that said mounting of the two members of each pair are on each of the left side and on the right side respectively of said at least one fixed

body member of the vehicle respectively, the members of each pair being mounted at the same longitudinal position of said vehicle;

- b) at least one pair of a safety beam upper elements said pair comprising two members of said pair, each member of said pair having a first face and a second face and designed to resist compression, and each of the members of said pair mounted to the first face of each member of a pair of said safety beam lower element on the left and the right sides of the vehicle;
- c) pairs of at least one passenger support mechanism each pair comprising two members, members of said pairs being mounted on each of the left and the right sides of said vehicle on at least one lateral axis such that the pair having its members closest to the external surface of the vehicle structure on any one of said lateral axes, constitutes the outermost pair on that lateral axis, and such that the pair having its members closest to the center of the vehicle structure on any one of said lateral axes constitutes an innermost pair;
- d) a plurality of impact decoupler/secondary slides each with a first face and a second face, attached by said first face to one member of said pair of said safety beam upper element on the second face of said safety beam upper element and said impact decoupler/secondary slides fixedly attached by said second face to one of the passenger support mechanisms, such that said impact decouplers/secondary slides are normally fixedly attached by said first face to said safety beam upper element, but become decoupled and thereafter slidably attached by said first face to said safety beam upper element along a lateral axis when a lateral shear force greater than a predetermined force is applied to said first face relative to said second face of said impact decouplers/secondary slides allowing said passenger support mechanisms attached to said second face of said impact decouplers/secondary slides to slide along said lateral axis relative to said safety beam upper element, said impact decouplers/secondary slides mounted on each of said safety beam upper element being constructed such that after they are decoupled, they can be guided laterally by, and are slidably attached to one or more of said safety beam upper element mounted on a single pair of said safety beam lower element, and further positioned on the safety beam upper element at all times such that they are not obstructed by any



elements of the vehicle in the event that said impact decouplers/secondary slides need under collision conditions to traverse the center of the vehicle to the further side of the vehicle;

- e) internal airbags, each mounted on the outer side of and adjoining each of the outermost said passenger support mechanisms, on both the left and the right sides of the vehicle, such that upon detection of an impact event, the airbag deploys one or more of upwards and inwards, next to said passenger support mechanism, to protect the passenger; and
- f) pairs of at least one protector assembly comprising a shock-absorbing device and a force distributing protector shield, each of said pairs comprising two elements, said elements of each pair being mounted on the left and the right side of the vehicle said protector assembly installed to protect each member of the outermost pair of passenger support mechanisms, on each of the left and right sides of the vehicle, and locked to the fixed body members of the vehicle to be oriented parallel to the sides of the passenger support mechanisms and adjoining said internal airbags, when in the operating position and positioned so as to not interfere with ingress and egress when said passenger support mechanisms are in the extended position.

40. **[WITHDRAWN/PREVIOUSLY RENUMBERED]** A vehicle structure as in claim 23, further comprising deflation devices that deflate said internal airbags installed on the side of said vehicle away from said lateral impact, immediately following an impact, when an outward movement of said passenger support mechanisms is detected, thereby providing more space for the motion of said passenger support mechanisms following said impact and minimizing ejection of said passenger support mechanism outside said vehicle.

41. **[NEW]** A vehicle with a vehicle structure supporting a passenger support mechanism with an occupant, said vehicle structure having an operating position attained

during normal driving conditions and an extended position attained at the time of occupant access to the vehicle, said vehicle structure having a means to separate an ejecting part of said passenger support mechanism from a non-ejecting part of said passenger support mechanism in the extended position of said vehicle structure such that at the time of egress and ingress to the vehicle by said occupant, the ejecting part displaces from said non-ejecting part to allow egress and ingress of said occupant without obstruction to said occupant, and said ejecting part having a means to provide lateral and vertical support to said occupant in the operating position.

42. [NEW] A vehicle with a vehicle structure as in 41, wherein said passenger support mechanism is decoupled from said vehicle during lateral impact thereby allowing said occupant in said passenger support mechanism to move in a predefined controlled manner to minimize injury.

43. [NEW] The vehicle structure of claim 1, further comprising:

- a) at least one pair of secondary slides, attached to the at least one fixed body member on the left side and the right side of the vehicle respectively, the members of each pair being mounted at the same longitudinal position of said vehicle;
- b) a plurality of passenger support mechanisms each having ejecting element and a non-ejecting element and each of said passenger support mechanisms mounted in pairs on each of the left and the right sides of the said vehicle on at least one lateral axis;
- c) a means to attach each of said secondary slides to each of said non ejecting element of said passenger support mechanism such that, said non-ejecting element is fixedly



attached to said secondary slide, but becomes decoupled and thereafter slidably attached to said secondary slide along a lateral axis when a lateral shear force greater than a predetermined force is applied to said non ejecting element with regard to said secondary slide allowing said non-ejecting part to slide along said lateral axis relative to said secondary slide;

- d) a means to attach each of said ejecting elements to said non-ejecting elements such that said ejecting elements may be displaced to allow egress and ingress of aid occupant without obstruction;
- e) at least one shock-absorbing device and at least one force distributing protector shield both installed to protect each of the pair of passenger support mechanisms, on each of the left and right sides of the vehicle, and locked to the fixed body members of the vehicle when in the operating position; and
- f) internal airbags, each mounted on the outer side of each of said passenger support mechanisms, but inside said shock absorbers and protector shields, on both the left and the right sides of the vehicle, such that upon detection of an impact event, the airbag deploys next to said passenger support mechanism(s) to protect the occupants.